

## Special Tec AA 10W-30

### Description

Modern premium-class fuel-efficient engine oil, which especially has been developed for the year-round use in Asian and American vehicles. The combination of unconventional base oils on synthesis technology in connection with the latest additives guarantees an engine oil which protects against wear, reduces the oil and fuel consumption, keeps the engine clean and provides for a quick oiling of the engine.

### Properties

- excellent wear resistance
- reduces pollutant emissions
- reduces fuel consumption
- excellent high and low temperature behavior
- mixable with all commercially available motor oils
- long engine service life
- tested for turbochargers and catalytic converters
- optimum stability to aging
- high lubrication reliability
- outstanding engine cleanliness
- rapid oil delivery at low temperatures
- stable against shear forces
- smooth engine running
- optimum oil pressure under all operating conditions

### Specifications and approvals:

API SN • ILSAC GF-5

### LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

API CF • Chrysler MS-6395 • Daihatsu • Ford • GM 6094 M • Honda • Hyundai • Isuzu • Kia • Mazda • Mitsubishi • Nissan • Subaru • Suzuki • Toyota

### Technical data

Viscosity SAE class	10W-30
Density at 15 °C	0,850 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	61,0 mm <sup>2</sup> /s DIN 51562
Viscosity at 100 °C	10,6 mm <sup>2</sup> /s DIN 51562
Viscosity at -30°C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -25°C (CCS)	<= 7000 mPas ASTM D 5293



### Technical data

Viscosity index	165 DIN ISO 2909
HTHS at 150°C	< 3,5 mPas ASTM D 5481
Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	11,1 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,3 mg KOH/g DIN ISO 3771
Color number (ASTM)	L 2,0 DIN ISO 2049

### Areas of application

Ideal for modern Japanese and American gasoline engines. Particularly suitable in case of long oil change intervals and high motor requirements.

### Application

The operational instructions of the car manufacturer and the engine manufacturer are to be observed.

**The full effectiveness of the product can only be guaranteed if it remains in unmixed condition!**

### Available pack sizes

1 l Canister plastic	7614 BOOKLET
1 l Canister plastic	7523 D-RUS-UA
4 l Canister plastic	7613 BOOKLET
4 l Canister plastic	7524 D-RUS-UA
5 l Canister plastic	8423 BOOKLET
205 l Drum sheet metal	7526 D-GB

# Product information

PI 12/07/12/2016



## Special Tec AA 10W-30

Our information is based on thorough research and may be considered reliable, although not legally binding.