

Throttle valve cleaner

DESCRIPTION

Special active solvent for cleaning typical contamination and deposits found in the intake and throttle valve areas. Dissolves and removes all smeary deposits and contaminants such as oil, resins, adhesive residues, etc. Also reliably cleans nozzles and internal components. Ensures the operability of all moving parts and reduces fuel consumption.

PROPERTIES

- Rapid and effective cleaning
- Cleaning without dismantling
- Easy to use and economical
- Suitable for use with catalytic converters

TECHNICAL DATA

Base	:	Mixture of solvents	
Form	:	Liquid/aerosol	
Color	:	Yellow	
Odor	:	Aromatic	
Density at 20 °C	:	0.87 g/cm ³	DIN 51757

APPLICATIONS

Removes contamination and deposits in the intake and throttle valve area. Only suitable for use in gasoline engines.

APPLICATION

Turn the engine off, thoroughly spray the parts to be cleaned and allow the agent to take effect for 2 to 3 minutes. Then restart the engine and generously spray the complete area again with the engine running at medium speed. Repeat cleaning in extreme cases.

Note: The spray extension can be detached from the spray nozzle, depending on the application area.

AVAILABLE PACK SIZES

Throttle valve cleaner	400 ml	aerosol can	Part no. 5111 D-GB-I-E-P
	200 ml	aerosol can	Part no. 2727 D-GB
	400 ml	aerosol can	Part no. 2846 D-DK-FIN-N-S
	400 ml	aerosol can	Part no. 7578 D-RUS-UA
	400 ml	aerosol can	Part no. 8986 D-NL-F-GR-ARAB

PI 04/04/09

Our information is based on thorough research and may be considered reliable, although not legally binding.

